


Wall Light--Touch Switch Control



Dimension



Rated Power: 4W
D-H(mm): $\Phi 130 \times 40$

Rated Power: 7W
D-H(mm): $\Phi 200 \times 40$

Rated Power: 10W
D-H(mm): $\Phi 300 \times 40$



Rated Power: 4W
D-H(mm): 130×40

Rated Power: 7W
D-H(mm): 200×40

Rated Power: 10W
D-H(mm): 300×40

Technical Details

IP65 RoHS CB CE CRI ≥ 80

30,000 Hrs | LM80 | B10

Basic Details



Wattage
4W | 7W | 10W



Luminous efficiency
80lm | 140lm | 200lm



CCT
3000K | 4000K | 6500K



Input Voltage
85-265V, 50/60Hz



Material
Iron+PS



Body Finish
White | Black | Gold | Brushed gold |
Wood grain | Marble

Mounting Information



Recessed



Suspended



Surface



Track



Self Adhesive
Double Sided Tape

Optional Selection



CCT



3000K

4000K

6000K

First time
turning on the light

Convert color
temperature

Convert color
temperature

Continuous touch
adjustment of
color temperature


OR

Long press
dimming

10%

100%


Installation Methods




1



2



3



4

1. Drill 4 mounting holes and insert expansion tubes into the holes. Then fix the hanging plate with screws.
2. Connect the cables (power supply, L/N/E) correctly.
3. Align the four screws on the hanger with the four holes on the lamp body and press the slot horizontally.
4. Tighten the screws and the installation is complete. Turn on the power and light up.

